



Safety Data Sheet

Reacted Plei-Tech™ Polyurethane Article

Version: 1.0

Date Prepared: 6/1/2015

Revision Date: 1/1/2021

Page: 1/5

1. Product and Company Identification

Company

Pleiger Plastics Company
498 Crille Road
Washington, PA, 15301, USA

Emergency Response Information

Phone 1-800-753-4437

Synonyms: Polyurethane Elastomer, Urethane Rubber, Urethane Elastomer, Polyurethane Foam

2. Hazards Identification

Emergency overview

CAUTION:
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

State of matter: Solid
Color: Varies
Odor: No characteristic Odor

Potential health effects

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation, primarily via dust from cutting and grinding operations. Routes of entry for gases, primarily via hot wire cutting or branding, include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Ingestion may cause gastrointestinal disturbances.

Irritation / corrosion:

Irritating to respiratory system. Irritating to eyes and skin. Contact with powders or dusts may irritate the eyes, skin and respiratory tract. Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Assessment other acute effects:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Sensitization:

The chemical structure does not suggest a sensitizing effect.

Chronic toxicity:

Carcinogenicity: The chemical structure does not suggest a specific alert for such an effect.

Repeated dose toxicity: No known chronic effects.

Reproductive toxicity: The chemical structure does not suggest such an effect.

Teratogenicity: The chemical structure does not suggest such an effect.

Genotoxicity: The chemical structure does not suggest such an effect.

Safety Data Sheet

Reacted Plei-Tech™ Polyurethane Article

Version: 1.0

Date Prepared: 6/1/2015

Revision Date: 1/1/2021

Page: 2/5

Medical conditions aggravated by overexposure:

Data available does not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this solid product. Dust from grinding may aggravate lungs when proper protection is not used.

Signs and symptoms of overexposure:

No significant reaction of the human body to the product known.
No hazards anticipated.

Potential environmental effects

Aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Degradation / environmental fate:

Poorly biodegradable.

3. Composition / Information on Ingredients

| <u>CAS Number</u> | <u>Content (W/W)</u> | <u>Chemical name</u> |
|--------------------------|-----------------------------|-----------------------------|
| N/A | 100.0 % | Polyurethane Elastomer |

4. First-Aid Measures

If inhaled:

After inhalation of decomposition products: Remove the affected individual into fresh air and keep the person calm. Seek medical attention if necessary.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Seek medical attention if necessary.

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

| | |
|----------------------------|-------------------|
| Flash point: | > 110 °C |
| Autoignition: | > 250 °C |
| Lower explosion limit: | not determined |
| Self-ignition temperature: | not self-igniting |

Suitable extinguishing media:

Water spray, dry powder, carbon dioxide, foam

Hazards during fire-fighting:

If product is heated above decomposition temperature, toxic vapors will be released.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Safety Data Sheet

Reacted Plei-Tech™ Polyurethane Article

Version: 1.0

Date Prepared: 6/1/2015

Revision Date: 1/1/2021

Page: 3/5

6. Accidental release measures

Personal precautions:

No special precautions necessary.

Cleanup:

Place into suitable container for disposal. See SDS section 13 - Disposal consideration.

7. Handling and Storage

Handling

Protection against fire and explosion:

No explosion proofing necessary.

Storage

General advice:

Avoid deposition of dust. No special precautions necessary.

Storage stability:

No data available.

8. Exposure Controls and Personal Protection

Advice on system design:

Provide local exhaust ventilation to control dust from grinding or fumes from hot wire/ knife operations to keep exposure below local TWA / STEL requirements.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator for grinding operations. For heated operations wear an air purifying respirator with an organic filter.

Hand protection:

Work gloves

Eye protection:

Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wash soiled clothing immediately.

9. Physical and Chemical Properties

| | | |
|--|------------------------------|----------------|
| Form: | solid | |
| Odor: | No characteristic odor | |
| Color: | Varies | |
| pH value: | >= 7 | |
| Melting temperature: | Degridation begins at 250 °C | |
| Boiling point: | > 200 °C | |
| Vapour pressure: | < 0.1 hPa | (25 °C) |
| Density: | approx. 1.05 – 1.28 g/cm3 | (20 °C) |
| Bulk density: | approx. 500 kg/m3 | (20 °C) |
| Vapour density: | | not applicable |
| Partitioning coefficient n-octanol/water (log Pow): | | not applicable |
| Viscosity, dynamic: | | not determined |
| Solubility in water: | | not soluble |
| Other Information: | None | |

Safety Data Sheet

Reacted Plei-Tech™ Polyurethane Article

Version: 1.0

Date Prepared: 6/1/2015

Revision Date: 1/1/2021

Page: 4/5

10. Stability and Reactivity

Conditions to avoid:

> 300 degrees Fahrenheit

Avoid extreme heat. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible with strong acids and bases

Hazardous reactions:

The product is chemically stable.

Decomposition products:

Thermal decomposition products: carbon monoxide, carbon dioxide, hydrogen cyanide, ether, esters, ketones

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

not fire-propagating

11. Toxicological information

Sensitization:

Result: Non-sensitizing.

Aspiration Hazard:

No aspiration hazard expected.

12. Ecological Information

Other adverse effects:

The product has not been tested. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:

Dispose of in a licensed facility, in accordance with all local, state, and federal regulations.

Container disposal:

Incinerate or dispose of in a licensed facility.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Safety Data Sheet

Reacted Plei-Tech™ Polyurethane Article

Version: 1.0

Date Prepared: 6/1/2015

Revision Date: 1/1/2021

Page: 5/5

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / exempt

16. Other Information

Recommended use: polyurethane component industrial chemicals
Suitable for use in industrial sector: Polymers industry; chemical industry

NFPA Hazard codes:

Health: 1 Fire: 1 Reactivity: 1 Special:

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. We support our customers in ensuring the safe and environmentally sound handling, storage, and transportation of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

PLEI-TECH PRODUCTS ARE NOT AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.

END OF DATA SHEET